

Fluid Compatibility and Resistance Chart for Balflex Thermoplastic Hoses

Recommended	Recommende	ed with Restrictions	Not Recomme	nded		
Acetic Acid	•	Ethyl Glycol	•	Oil of Turpentine	•	
Acetic Acid (30%)	•	Ethyleneoxide	•	Oleic Acid	•	
Acetone	•	Fluorine	•	Oxalic Acid	•	
Acetylene	•	Formaldehyde	•	Perchloroethylene	•	
Ammonia, Gas (Hot)		Formaldehyde 40%	•	Phenol	•	
Ammonia, Liquid	•	Fuel Oil	•	Phosphoric Acid (10%)		
Ammoniumchloride	•	Gaseous Hydrogen	•	Phosphoric Acid (70%)	•	
Amyl Acetate		Gasoline		Phosphate Ester Base Oil	•	
Aniline	•	Glycerin / Glycerol	•	Saturated Steam	•	
Animal Oils	•	Glycol to 66°C	•	Sea Water	•	
Benzol / Benzene	•	Hexane	•	Silicone Oils		
Butane	•	Hydraulic Oil	•	Soap Solutions	•	
Butyl Acetate		Hydrochloric Acid 37%	•	Soda	•	
Butyl Alcohol / Butanol		Hydroger Peroxide (Dil.)		Sodium Chloride Solutions	•	
Calcium Chloride Solutions	•	Hydroger Peroxide (Conc.)		Sodium Hydroxide 20%		
Carbon Dioxide		Isocyanates	•	Sodium Hypochloryde 10%		
Carbon Disulfide		Isopropil Alcohol		Sulphur	•	
Carbonates		Kerosene	•	Sulphur Dioxide		
Caustic Soda	•	Liquid Oxygen		Sulphuric Acid up to 50%	•	
Chlorinated Solvents		LPG		Sulphuric Acid above 50%	•	
Chlorine	•	Lubricating Oils	•	Toluene	•	
Chloroform	•	Mercury	•	Trichloroethylene	•	
Citric and Solutions	•	Methyl Alcohol / Methanol	•	Vegetable Greases		
Compressed Air	•	Methyl Chloride (Cold)	•	Water	•	
Cyclohexane	•	Methyl Ethyl Khetone	•	Xylene	•	
Crude Petroleum Oil	•	Mineral Oils	•	The following data is based on tests and believed to be reliable; however the tabulation should be used as a guide ONLY since it does not take into consideration all variables, such as elevated temperatures, fluid contamination, concentration, etc. that may be encountered in actual use. All critical applications should be tested. Note: All data based on 20°C/70°F unless		
Dioctyl Phthalate	•	Naphtha	•			
Diesel Fuel	•	Naphthalene	•			
Ethers		Natural Gas	•			
Ethyl Acetate		Nitric Acid (Dil.)	•			
Ethyl Alcohol	•	Nitric Acid (Conc.)	•			
Ethyl Chloride		Nitrobenzen				