





All dimensions are in (mm)

		VALUES	1/4"	3/8"	1/2"	5/8"	3/4"	1"	1.1/4"	1.1/2"	2"
			-4	-6	-8	-10	-12	-16	-20	-24	-32
10.1002		FERRULE	BF21.04	BF21.06	BF21.08	BF21.10	BF21.12	BF21.16			
		CRIMPING DIAMETER	16.7	21.2	24.3	27.2	31.9	40.7			
R1AT / 1SN											
10.1004		FERRULE	BF21.04	BF21.06	BF21.08	BF21.10	BF21.12	BF21.16			
		CRIMPING DIAMETER	17.7	22.2	25.3	28.2	32.9	41.7			
R2AT / 2SN											
10.1017		FERRULE	BF21.04	BF21.06	BF21.08	BF21.10	BF21.12	BF21.16			
		CRIMPING DIAMETER	16.7	20.1	23.0	27.2	31.9	40.7			
R17											
10.1019 10.1010		FERRULE	BF21.04	BF21.06	BF21.08	BF21.10	BF21.12	BF21.16			
		CRIMPING DIAMETER	16.7	21.2	24.3	27.2	31.9	40.7			
R16 / 2SC IMPACTUS											



Dimensions [mm]: tolerance +0.25/-0.25

The indicated crimping diameters must be understood as indicative, because of the big range tolerances of hose specifications indicated in the SAE / DIN / EN standard, Balflex recommends hydrostatic testing according to ISO 1402.

* On sizes – 12 (3/4") the Balflex® POWERSPIR DIN EN 856 4SH and SAE 100R13 and SAE 100R15 hoses are the same.

**On sizes – 16 (1") the Balflex® POWERSPIR DIN EN 856 4SH and SAE 100R13 hoses are the same.

Instructions

FERRULE	BW.12	BALFLEX CODE
HOSE O.D.	≤ 30.6	Dimensions in mm
CRIMPING DIAMETER (mm)	34.0	Dimensions in mm
EXTERNAL SKIVING	--	Dimensions in mm

BALFLEX® FULL CRIMP

